



### 技术参数 Specifications

使用线数 (Hole count): 2 3 6  
 温度范围 (Temperature range): -25°C ~ 85°C  
 额定电压 (Rated voltage): 300V. AC/DC  
 额定电流 (Rated current): 5A

### 端子 Terminal

图号 Pic	型号 Type	描述 Description	厚度 Thickness	材质 Material	表面处理 Surface treatment	压线范围 WireRange		尺寸 Dimension(mm)			对照表 Comparison No.	最小包装量 Minimum packing
						AWG#	mm <sup>2</sup>	W	L	E		
A	DJ611-1.8A/BL8	横连式 Horizontal chain	0.3	黄铜 Brass	镀亮锡 Bright tin plating	22~20	0.3~0.5	1.8	23.1	7.2	公头 Male	4500
B	DJ621-1.8A	横连式 Horizontal chain	0.25	磷铜 Phosphor copper	镀亮锡 Bright tin plating	22~20	0.3~0.5	2.7	19.1	7.9	母座 Female	4000

### 塑料件 Plastic parts

线数 Hole count	公头 Plug for male terminal	母座 Receptacle for female terminal
2	DJ7021-1.8-11 	DJ7021-1.8-21 
3	DJ7031-1.8-11 	
6	DJ7061-1.8-11 	DJ7061-1.8-21 